



Speciality Aquaculture
Equipment Supplier



Ecotao Enterprises cc
CK 2001/053814/23
PO Box 1524
7 Waterboom Street
Stanger
4450
www.ecotao.co.za
web@ecotao.com

B02A01~B02A20

Feature: Ring Blowers are designed with practical regenerative theory. Require no maintenance.
No oily odor. Long lifespan.

SPECIFICATION

ITEM#	In/Out Let	Phase P	Frequency Hz	Voltage V	Power KW/HP	Current A	Pressure (max) mm H ₂ O	Air Flow (max) m ³ /min	Noise Level dB	Weight Kgs	UNIT	PRICE
B02A01	1"	1 ϕ	50/60	110/220	0.18 (1/4HP)	2.4/1.2	500/700	0.6/0.8	60/65	9	set	
B02A02	1-1/4"	1 ϕ	50/60	110/220	0.37 (1/2HP)	5/2.5	1000/1200	1.3/1.5	68/70	15	set	
B02A03	1-1/2"	1 ϕ	50/60	110/220	0.74 (1HP)	14/7	1600/1800	2.4/2.6	67/72	20	set	
B02A04	2"	1 ϕ	50/60	110/220	1.50 (2HP)	30/15	2000/2500	3.2/4.5	70/75	35	set	
B02A11	1"	3 ϕ	50/60	220	18 (1/4HP)	1.2	500/700	0.6/0.8	60/65	9	set	
B02A12	1-1/4"	3 ϕ	50/60	220	0.37 (1/2HP)	1.8	1000/1200	1.3/1.5	65/70	15	set	
B02A13	1-1/2"	3 ϕ	50/60	220	0.74 (1HP)	3	1600/1800	2/2.2	67/72	20	set	
B02A14	2"	3 ϕ	50/60	220	1.5 (2HP)	5.4	2000/2500	3.2/4.5	70/75	30	set	
B02A15	2"	3 ϕ	50/60	220	2.2 (3HP)	8	2500/2800	5/6.2	70/75	35	set	
B02A16	2"	3 ϕ	50/60	220	3.7 (5HP)	13	2800/3500	7/8.3	77/78	55	set	
B02A17	2-1/2"	3 ϕ	50/60	220	5.5 (7-1/2HP)	19	2600/3200	7.5/9.5	80/85	85	set	
B02A18	2-1/2"	3 ϕ	50/60	220	7.5 (10HP)	24	2900/3400	9/11	80/85	95	set	
B02A19	4"	3 ϕ	50/60	220	11 (15HP)	36	2500/3000	20/24	82/87	175	set	
B02A20	4"	3 ϕ	50/60	220	15 (20HP)	47	3000/3500	25/28	82/87	182	set	

Please Note: As policy of continuous improvement is followed, and the right to alter any published data without notice is reserved. The Maximum permissible temperature and the inlet gas temperature is 40°C

Ecotao Enterprises cc (VAT no: 4590247682)

PO Box 1524, Stanger, 4450, South Africa

| Tel: 27-32-5525929 | Skype: [ecotao](https://www.skype.com/name/ecotao) | email: web@ecotao.com | Mobile: 27-823903989